

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): A mobile unit ~~that is capable of communication using~~
a plurality of communication subsystems, comprising ~~characterized in that it comprises:~~

determination means that determines usability of the plurality of communication
subsystems at the current location of said mobile unit;

selection means that selects a communication subsystem whereby the current location
can be measured with the greatest accuracy, of the communication subsystems that are
determined as usable by said determination means; and

transmission means that ~~infers~~ measures said current location using the
communication subsystem selected by said selection means and transmits the result of
determination of said usability by said determination means, together with information
indicating said current location, using the communication subsystem selected by said
selection means.

Claim 2 (Currently Amended). A server, comprising ~~characterized in that it~~
~~comprises:~~

communication means that receives the result of determination of said usability
transmitted by the transmission means of the mobile unit according to claim 1, together with
information indicating said current location; and

storage means that stores in updateable fashion the result of determination of said
usability received by said communication means as geographical information, in
correspondence with information indicating said current location.

Claim 3 (Currently Amended): The server according to claim 2, further comprising:
~~characterized in that, it further comprises~~

communication subsystem specification means that specifies a communication subsystem that is usable at said current location or at a location designated by said mobile unit, by looking up the geographical information stored in said storage means; and,

said communication means notifies said mobile unit of the usable communication system specified by said communication system specification means, in response to a request from the mobile unit.

Claim 4 (Currently Amended). A server, comprising ~~characterized in that it comprises:~~

communication means that receives the result of determination of said usability transmitted by transmission means of a mobile unit according to claim 1, together with information indicating said current location;

region specification means that specifies a geographical region to which the current location belongs, based on information indicating said current location received by said communication means; and;

storage means that stores in updateable fashion as frequency-of-use information the number of times per unit time that a usability determination result has been received by said communication means, in correspondence with the usable communication subsystem indicated by said determination result and the geographical region specified by said region specification means.

Claim 5 (Currently Amended). The server according to claim 4, wherein:
~~characterized in that,~~

said region specification means specifies the frequency-of-use of the each communication subsystem in the geographical region to which said current location or the location designated by said mobile unit belongs by looking up frequency-of-use information stored in said storage means; and

said communication means notifies said mobile unit of the frequency-of-use specified by said region specification means in response to a request from the mobile unit.

Claim 6 (Currently Amended): A method of information provision ~~characterized in that, for~~ a mobile unit ~~that is~~ capable of communication using a plurality of communication subsystems, comprising comprises:

at the mobile station,

a determination step of determining usability of the plurality of communication subsystems at the current location of said mobile unit;

a selection step of selecting a communication subsystem whereby the current location can be most accurately measured, of the communication subsystems determined as usable in said determination step; and

a transmission step of ~~inferring~~ measuring said current location using the communication subsystem selected in said selection step and transmitting the result of determination of said usability in said determination step, together with information indicating said current location, using the communication subsystem selected in said selection step, and

at a server, comprises:

a reception step for receiving the determination result of said usability transmitted in said transmission step, together with information indicating said current location;

a storage step of storing in storage means in updateable fashion as geographical information the result of determination of said usability received in said reception step, in correspondence with information indicating said current location;

a communication subsystem specification step of specifying a communication subsystem that can be used at said current location or at a location designated by said mobile unit, by looking up the geographical information stored in said storage means; and

a notification step of notifying said mobile unit of a usable communication subsystem specified in said communication subsystem specification step, in response to a request from the mobile unit.

Claim 7 (Currently Amended): A method of information provision ~~characterized in that, for~~ a mobile unit ~~that is~~ capable of communication using a plurality of communication subsystems, comprising ~~comprises~~:

at the mobile station,

a determination step of determining usability of the plurality of communication subsystems at the current location of said mobile unit;

a selection step of selecting a communication subsystem whereby the current location can be most accurately measured, of the communication subsystems determined as usable in said determination step; and

a transmission step of ~~inferring~~ measuring said current location using the communication subsystem selected in said selection step and transmitting the result of determination of said usability in said determination step, together with information indicating said current location, using the communication subsystem selected in said selection step, and

at a server, ~~comprises~~:

a reception step for receiving the determination result of said usability transmitted in said transmission step, together with information indicating said current location;

a region specification step of specifying a geographical region to which the current location belongs, based on the information indicating said current location received in said reception step;

a storage step of storing in storage means in updateable fashion as frequency-of-use information the number of times per unit time that the result of determination of usability has been received in said reception step, in correspondence with the usable communication subsystem indicated by said determination result and the geographical region specified in said region specification step;

a frequency specification step of specifying the frequency-of-use of the each communication subsystem in the geographical region to which said current location or the location designated by said mobile unit belongs, by looking up the frequency-of-use information stored in said storage means; and

a notification step of notifying said mobile unit of the frequency-of-use specified in said frequency specification step, in response to a request from the mobile unit.